

PRODUCT	COMPOSITION	TACK FREE	CURE TIME	ELONGATION %
<b>ROOFING</b>				
PRO FLEX SEALANT	TRIPOLYMER	45 Mins.	5 Days	Clear - 1,062 Colors - 1,180
* PRO FLEX MULTI-PURPOSE BRUSH REPAIR COATING	TRIPOLYMER	2 Hrs.	4 Days	775
* INSTANT ROOF REPAIR BRUSHABLE COATING	TRIPOLYMER	4 Hrs.	5 Days	583
3300 PROFESSIONAL GRADE SEALANT	POLYURETHANE	3 Hrs.	1 Day	881
3500 BONDING SEALANT	POLYURETHANE	40 Mins.	1 Day	827
Geocel 4500 ROOF BONDING SEALANT	SCYPOLYMER	90 Mins.	1 Day	Black - 559 White - 465
4525 SEMI-SELF-LEVELING SEALANT	SCYPOLYMER	1 Hr.	Varies	408
45P TPO & PVC PRIMER	N/A	N/A	N/A	N/A
* ROOF PATCH	ASPHALTIC	1 Hr.	3 Days	N/A
ROOF PRO SEALANT	TRIPOLYMER	45 Mins.	4 Days	1,062
S2 SOLAR PANEL SEALANT	TRIPOLYMER	45 Mins.	4 Days	Clear - 1,062 Colors - 1,180
S4 SOLAR PANEL SEALANT	SCYPOLYMER	90 Mins.	4 Days	230
Geocel Shingle & Flashing Paint	AEROSOL	15 Mins.	2 Hrs.	N/A
Geocel Rust Converter	AEROSOL	3 Hrs.	1 Day	N/A
Geocel Galvanizing Primer	AEROSOL	15 Mins.	7 Days	N/A
Geocel Asphalt Primer	AEROSOL	N/A	1 Day	N/A
<b>GUTTERS</b>				
* INSTANT GUTTER SEAL	TRIPOLYMER	15 Mins.	5 Days	900
Geocel PRO GUTTER SEAL	SCYPOLYMER	45 Mins.	3 Days	418
<b>SIDING/WINDOWS/DOORS</b>				
* Geocel SWD SEALANT (formally ProCOLOR SWD)	TRIPOLYMER	30 Mins.	5 Days	455
WINDOW & DOOR FOAM	POLYURETHANE	5 Mins.	1 Day	N/A
<b>MASONRY/CONCRETE</b>				
1500SL SELF-LEVELING SEALANT	SCYPOLYMER	2 Hrs.	4 Days	730
3900 TEXTURED SEALANT	Polyurethane	4 Hrs.	1 Day	404
MORTAR SEAL SEALANT	ACRYLIC	20 Mins.	6 Days	116
<b>GENERAL CONSTRUCTION</b>				
ALL-IN-ONE BONDING SEALANT	ACRYLIC	Clear - 60 Mins. Colors - 80 Mins.	4 Days	Clear - 675 Colors - 980
EXPANDING FOAM	POLYURETHANE	5 Mins.	1 Day	N/A
* WATER SHIELD SEALANT	TRIPOLYMER	15 Mins.	4 Days	236
* WATER SHIELD BRUSHABLE REPAIR COATING	TRIPOLYMER	45 Mins.	2 Days	413
4300 CLEAR SEALANT	SCYPOLYMER	40 Mins.	N/A	359
4350 CONSTRUCTION SEALANT	SCYPOLYMER	90 Mins.	4 Days	230
8125 ACETOXY CURE SEALANT	SILICONE	25 Mins.	1 Day	469
8150 NUETRAL CURE SEALANT	SILICONE	1 Hr.	1 Day	Clear - 709 Colors - 608

\* Pro Flex & S2 Colors may not be sold in the state of California.  
Pro Flex, Roof Pro, & S2 Crystal Clear are exempt from this rule except in SCAQMD counties.  
\* This product may not be sold in the state of California.



**Proven Products for Proven Results.**

For over 40 years, the Geocel brand of caulks and sealants has given professional contractors an advantage with every job they finish. They know the performance they expect will be there everytime and every product will deliver solid results that support their goals of saving time, lowering costs, and most importantly no callbacks. They enjoy peace of mind and pride in realizing the workmanship of a job well done and that we are only a phone call away anytime sales or technical support is needed.

Whether it's for tough construction or repair applications, Geocel products perform as promised and as expected. We work side-by-side with professional contractors to develop products they enjoy working with and ensure that each product has the performance characteristics they need and want.

Why risk headaches down the road by working with an unproven sealant today? Look to the one who is setting the standard in caulk and sealant solutions. Look to Geocel.

Inside & Out...  
the Applications  
are Covered.





# PRODUCT | PERFORMANCE | INNOVATION

## ROOFING



**Pro Flex® Sealant**  
**"The Work Horse of Sealants"**  
 Stands the test of time with excellent adhesion, flexibility, UV resistance, and mildew resistance. Adheres to damp or oily surfaces, is paintable, resealable, and works on over 20 different substrates, including asphalt. Comes in Crystal Clear and Standard colors.



**3300® Professional Grade Polyurethane Sealant**  
 This high performance sealant offers minimal shrinkage. Its non-sag formula meets ASTM C 920. Ideal for larger joints in roofing, siding, & window applications.



**Geocel S2™ & S4™ Solar Panel Sealants**  
**Geocel S2™ Solar Panel Sealant**  
 Clear, solvent-based sealant that seals penetrations, flashings, brackets, and other mounting systems with excellent adhesion. Applies in damp, dirty, or oily conditions. Remains flexible, won't crack.  
**Geocel S4™ Solar Panel Sealant**  
 Contractor grade sealant for penetrations, flashings, brackets, and other mounting systems. Available in black. Applies in damp or dirty conditions, fast curing, & remains flexible. ASTM C 920 compliant.



**Geocel 4500® Roof Bonding Sealant**  
 This lap adhesive or scrim edge sealant applies, adheres & cures underwater. It needs no additional adhesives or sealants and is a non-flammable formula. Works on EPDM, Primed TPO & PVC, metal, asphalt shingles, concrete, & more.



**Geocel® Aerosols**  
**Geocel Shingle & Flashing Paint** - Hides flaws, blemishes & unsightly roof protrusions. Smooth, durable, rust fighting finish that prevents stains. Dries in 8 minutes or less.  
**Geocel Rust Converter** - Makes unsightly surfaces look new again. Converts rust in one easy step. Protects against further corrosion. Sprays clear, dries black.  
**Geocel Galvanizing Primer** - Eliminates worries of rust corrosion. Prevents rust creepage even on scratched surfaces. Dries in 15 minutes.  
**Geocel Asphalt Primer** - Adheres to porous and non-porous surfaces. Provides maximum bond to asphalt, concrete, masonry, and metal surfaces. 100% asbestos free.



**Geocel 4525™ Semi-self-leveling Sealant**  
 A hybrid, patent-pending sealant for repairs with no priming or mixing. Can be applied in damp or dry conditions and will remain flexible & not distort. Available in black.



**45P® TPO & PVC Primer**  
 After using primer, sealant may be applied immediately with no need for additional cleaners resulting in reduced job time and cost. 45P® is compatible with 4500® Roof Bonding Sealant & 4525™ Semi-self-leveling Sealant.



**Instant Roof Repair Brushable Coating (Fibred)**  
 Fibred for strong, flexible small-area roof repairs this product is a one-step application that stops leaks fast. No primer needed on most surfaces. Excellent adhesion even when damp.



**3500™ Polyurethane Bonding Sealant**  
 Is ideal for adhering roof tiles and in roofing, gutter, expansion joint, and construction joint applications. Fast set-up with minimal shrinkage. Meets ASTM C 920 & TT-S-00230C, Type II specifications.



**Complete System for Easy Pitch Pocket Installation**



**Pro Flex® Multi-Purpose Brushable Repair Coating**  
 A brushable version of Pro Flex® that prevents rust & staining. It is asphalt shingle compatible & paintable. Use to rustproof & waterproof surfaces. For small area use only.

**Geocel Pro Fit® Pocket System**  
 The patented Pocket is flexible & easily installed. No flashing, complex cutting, or difficult assembly is required. Create single or multiple pockets with either 2" or 4" height and 56" lengths. Each system includes the patented Pro Fit® Pocket, 4500® Sealant, 4525™ Sealant, a trowel, & 4 screws. Packaged for easy carrying with a shoulder strap.



**Roof Patch**  
 This asphalt-based, asbestos-free roof cement for wet or dry surfaces resists water quickly. Remains soft & pliable to resist temperature changes. Meets spec ASTM A-4586 Type I, Class II. Available as a brushable.



**Roof Pro™ Tripolymer Sealant**  
 Use for roofing applications with minimal surface preparation. A tough, durable, watertight seal with excellent adhesion in most weather conditions.

## MASONRY-CONCRETE



**Mortar Seal™ Silicized Acrylic Sealant**  
 A texturized acrylic sealant that looks like mortar, is flexible, cleans up easily with water, and is paintable. For moving and non-moving joints. ±12 1/2% joint movement.



**3900™ Texturized Polyurethane Sealant**  
 Texturized to look like mortar. Remains flexible & is paintable. Use for non-structural repairs.



**1500SL™ Premium Self-leveling Concrete Joint & Crack Sealant**  
 This self-leveling, moisture curing sealant is for horizontal concrete floor joints and cracks. It is non-gassing, remains flexible, and needs no priming on most substrates. Available in black and gray.

## SIDING/WINDOW/DOOR



**Window & Door Foam**  
 Expands minimally to eliminate frame distortion during installation. Use to stop air infiltration around doors, window frames, and pipe penetrations. Features R-value of 4 to 5.



**Geocel SWD™ Sealant**  
 Excellent adhesion to many siding, window & door substrates. It remains flexible, won't pull away and is ASTM C 920 compliant. Available in white only. Formerly labeled as ProCOLOR SWD.

## GUTTERS



**Geocel Pro® Gutter Seal**  
 Applies, adheres and cures underwater. It is fast curing, and remains flexible. It is weather and UV resistant with minimal shrinkage. Also recommended for metal awnings, vents, & flashing. Not for potable water use.



**Instant Gutter Seal**  
 Designed to prevent the passage of air and moisture in small joints and seams. Excellent adhesion, even when surface is damp. It is UV resistant, paintable, and semi-self-leveling. Not for potable water use.

## GENERAL CONSTRUCTION



**Water Shield® Caulking Sealant**  
 100% resealable, paintable, & gunnable at low temperatures with good adhesion to many building materials. Designed for most moving & non-moving joints. Adheres to damp & non-porous surfaces



**Water Shield® Brushable Repair Coating**  
 A semi-self-leveling repair coating for small areas. It forms a tough, flexible film with excellent adhesion to a variety of materials. Stops leaks fast. For use in construction, commercial, agricultural, manufacturing, & industrial applications.



**8125® 100% Silicone High Performance Acetox Cure Sealant**  
 100% construction grade silicone. This high modulus, ±25% joint movement sealant meets ASTM C920, Type S, Grade NS, Class 25, Use NT, G, A, Fed Specs TT-S-001543A and TT-S-00230C, Type II. CAN/CGSB-19.13-M-87, Class MG-2-25-A-L. Certified by NSF. After fully cured & washed, meets FDA Regulations No. 21 CFR 177.2600 subject to end use.



**8150® 100% Silicone High Performance Neutral Cure Sealant**  
 100% construction grade silicone. This high modulus, ±25% joint movement sealant meets U.S. Fed. Spec. TT-S-001543A (COM-NBS) Class A and TT-S-00230CC (COM-NBS) Class A. ASTM C 920, Type S, Grade NS, Class 25 Use NT, M, G, A, O. CAN/CGSB-19.13-M87, Class MCG-2-25-A-L.



**Geocel 4350™ Construction Sealant**  
 This UV resistant, interior/exterior sealant is available in 8 standard colors and is paintable. Remains flexible, is fast curing, and adheres in damp or dry conditions. Meets ASTM C 920 specifications.



**Geocel 4300™ Clear Sealant**  
 Clear sealant with minimal shrinkage. Fast curing, remains flexible. Excellent adhesion, is paintable, and adheres in damp or dry conditions. Meets ASTM C 920.



**all-in One™ Adhesive/Sealant**  
 For adhesive and sealant applications, indoors and out, it is water resistant in 3 hours and paintable in 10 minutes. Works on drywall, foam/insulation board, galvanized steel, and other common materials



**Expanding Foam Sealant**  
 This polyurethane foam expands up to 3 times to fill large voids & holes. It also features an R-value of 4 to 5. Use to stop air infiltration around doors & window frames and pipe penetrations.

\* Product may not be sold in the state of California.

† Pro Flex Sealant and S2 Colors may not be sold in the state of California. Pro Flex Sealant, S2, and Roof Pro Crystal Clear are exempt from this rule except in SCAQMD counties.

